

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

1. (original) A transmission apparatus for use in a communication network to which a plurality of transmission equipment are connected through a plurality of transmission lines transmitting synchronous multiplex signals, wherein overhead for supervision, maintenance and operations of transmission equipment and transmission lines is added to a payload in which main signals are multiplexed, said transmission apparatus comprising:

an optical transmitter that transmits said synchronous multiplex signals to said transmission lines,

an optical receiver that receives said synchronous multiplex signals from said transmission lines,

an overhead processing unit that adds said overhead to said payload and extracts said overhead out of said synchronous multiplex signals from said optical receiver,

a cross connect unit that divides and multiplexes said payload inputted from said overhead processing unit, switches output routes of said payload for transmission to either of said transmission lines, and outputs to the overhead processing unit again,

a clock unit that supplies a clock to at least said cross connect unit,

an equipment supervision unit that supervises at least said cross connect unit and said clock unit and outputs an instruction signal based upon the result of the supervision,

a switching control unit that controls switching of the transmission lines so that, being based upon said instruction signal and said overhead, said cross connect unit, said overhead processing unit and said optical transmitter, said synchronous multiplex signals may be transmitted to either of said transmission lines properly; and wherein

upon said equipment supervising unit detecting a condition in which obstacles have occurred in more than one group in at least either of said cross connect unit and said clock unit, said equipment supervision unit inserts information about said obstacles in said instruction

signal, and said switching control unit into which said instruction signal is inputted enables said overhead processing unit and the optical transmitter to output isolation instruction information to said transmission line.

2. (original) A transmission apparatus according to claim 1, said transmission apparatus and an adjacent transmission equipment being interconnected by two optical fibers; wherein the capacity of each line is divided into two, one half thereof being used as a working line and the remaining half thereof being used as a protection line; and wherein, upon occurrence of said obstacle, said isolation instruction information further comprising said overhead indicating that said synchronous multiplex signals to be received are both in a signal obstacle condition.

3. (original) A transmission apparatus according to claim 1, said transmission apparatus and an adjacent transmission equipment being interconnected by four optical fibers, each being used as a working line or a protection line; and wherein, upon occurrence of said obstacle, said isolation instruction information further comprising said overhead indicating that said synchronous multiplex signals to be received are both in a signal obstacle condition.

4. (original) A transmission apparatus for a network according to claim 1, said transmission apparatus and an adjacent transmission equipment being interconnected by two optical fibers; wherein the capacity of each line is divided into two, one half thereof being used as a working line and the remaining half thereof being used as a protection line; and wherein, upon occurrence of said obstacle, said isolation instruction information further comprising said overhead for instructing a ring switch transmitting, upon reception, the received synchronous multiplex signals.

5. (original) A transmission apparatus for a network according to claim 1, said transmission apparatus and an adjacent transmission equipment being interconnected by four optical fibers, each being used as a working line or a protection line; and wherein, upon

occurrence of said obstacle, said isolation instruction information further comprising said overhead for instructing a ring switch transmitting, upon reception, the received synchronous multiplex signals.

6. (original) A transmission apparatus for a network according to claim 1, said transmission apparatus and an adjacent transmission equipment being interconnected by two optical fibers; wherein the capacity of each line is divided into two, one half thereof being used as a working line and the remaining half thereof being used as a protection line; and wherein, upon occurrence of said obstacle, said isolation instruction information further comprising said overhead indicating that said synchronous multiplex signals to be transmitted are in a signal obstacle condition.

7. (original) A transmission apparatus for a network according to claim 1, said transmission apparatus and an adjacent transmission equipment being interconnected by four optical fibers, each being used as a working line or a protection line; and wherein, upon occurrence of said obstacle, said isolation instruction information further comprising said overhead indicating that said synchronous multiplex signals to be transmitted are in a signal obstacle condition.

8. (original) A transmission apparatus for a network according to claim 1, said transmission apparatus and an adjacent transmission equipment being interconnected by two optical fibers; wherein the capacity of each line is divided into two, one half thereof being used as a working line and the remaining half thereof being used as a protection line, or the transmission equipment are interconnected by four optical fibers, each being used as a working line or a protection line; and wherein, upon occurrence of said obstacle, said isolation instruction information further comprising a no-signal condition caused by stopping the transmission of said optical transmitter.

9. (original) A transmission apparatus for a network according to claim 1, said transmission apparatus and an adjacent transmission equipment being interconnected by

four optical fibers, each being used as a working line or a protection line; and wherein, upon occurrence of said obstacle, said isolation instruction information further comprising a no-signal condition caused by stopping the transmission of said optical transmitter.

10. (original) A transmission apparatus for a network according to claim 1, wherein said transmission apparatus, upon occurrence of said obstacle, prepares as said isolation instruction any of the following:

said isolation instruction information is said overhead, wherein said overhead indicates that said received synchronous multiplex signals are both in signal obstacle conditions,

said isolation instruction information is said overhead, wherein said overhead instructs a ring switch, in which synchronous multiplex signals are transmitted upon reception,

said isolation instruction information is said overhead, wherein said overhead indicates that said synchronous multiplex signals to be transmitted are in a signal obstacle condition, and

said isolation instruction information is a no output signal condition caused by stopping the transmission of said optical transmitter.

11. (currently amended) A telecommunication network transmission system, said network transmission system having a plurality of transmission apparatuses, each of said plurality of transmission apparatus operative to transmit synchronous multiplex signals, wherein in said transmission apparatus, an overhead for supervision, maintenance and operations of transmission apparatuses and transmission lines is added to payload in which main signals are multiplexed, said transmission apparatus comprising:

a plurality of optical transmitters,

a plurality of optical receivers,

a cross connect unit that divides and multiplexes said payload input received from at least one of said plurality of optical receivers, and thereupon switches output to any of said plurality of transmission apparatuses,

a clock unit that supplies a clock signal to at least said cross connect unit,

an equipment supervision unit that supervises at least said cross connect unit and said clock unit;

wherein responsive to detection of a condition in which obstacles have occurred in more than one group, in at least one of said plurality of transmission apparatuses, said equipment supervision unit comprised in the transmission apparatus having said obstacles creates optical transmitter output isolation instruction information in order to isolate said transmission apparatus itself in which obstacles have occurred in more than one group, from said network.

91 com-7
12. (original) A telecommunication system according to claim 11, wherein said isolation instruction information further comprises said overhead, and wherein said overhead indicates that said synchronous multiplex signals to be received are in a signal obstacle condition.

13. (original) A telecommunication system according to claim 11, wherein said isolation instruction information further comprises said overhead, and wherein said overhead instructs a ring switch to transmit, upon reception, received synchronous multiplex signals.

14. (original) A telecommunication system according to claim 11, wherein said isolation instruction information further comprises said overhead, and wherein said overhead indicates that said synchronous multiplex signals to be transmitted are in a signal obstacle condition.

15. (currently amended) A telecommunication system according to claim 11, wherein said isolation instruction information further comprises an indication of a no-signal ~~no signal~~ condition caused by stopping the transmission of said optical transmitter due to a fault condition.

16. (original) A telecommunication system according to claim 11, wherein said transmission apparatus, upon occurrence of said obstacle, prepares as said isolation instruction any of the following:

said isolation instruction information is said overhead indicating that said received synchronous multiplex signals are both in signal obstacle conditions,

said isolation instruction information is said overhead instructing a ring switch, in which synchronous multiplex signals are transmitted upon reception,

said isolation instruction information is overhead indicating that said synchronous multiplex signals to be transmitted are in a signal obstacle condition, and

said isolation instruction information is a no output signal condition caused by stopping the transmission of said optical transmitter.

Q1 am. f
17. (original) A network transmission system, comprising:
a plurality of nodes, wherein upon a fault condition in which obstacles have occurred in more than one group in at least one of said plurality of nodes, said node suffering said fault condition isolates itself from others of said plurality of nodes in said network transmission system.

18. (currently amended) An network transmission system according to claim 17, said network transmission system having a plurality of nodes, wherein each of said plurality nodes is operative to transmit synchronous multiplex signals, wherein in said nodes, an overhead for supervision, maintenance and operations of nodes and transmission lines is added to payload in which main signals are multiplexed, each of said nodes comprising:

a plurality of optical transmitters,

a plurality of optical receivers,

a cross connect unit that divides and multiplexes said payload input received from at least one of said plurality of optical receivers, and thereupon switches output to any of said plurality of nodes,

a clock unit that supplies a clock signal to at least said cross connect unit,

an equipment supervision unit that supervises at least said cross connect unit and said clock unit;

wherein responsive to detection of a condition in which obstacles have occurred in more than one group, in at least one of said plurality of nodes, said equipment supervision unit

comprised in the node having said obstacles creates optical transmitter output isolation instruction information in order to isolate said ~~nodes~~ node itself in which obstacles have occurred in more than one group, from said network.

19. (original) An network transmission system according to claim 17, wherein said isolation instruction information further comprises said overhead indicating that said synchronous multiplex signals to be received are in a signal obstacle condition.

20. (original) An network transmission system according to claim 17, wherein said isolation instruction information further comprises said overhead instructing a ring switch transmitting, upon reception, the received synchronous multiplex signals.

21. (original) An network transmission system according to claim 17, wherein said isolation instruction information further comprises said overhead indicating that said synchronous multiplex signals to be transmitted are in a signal obstacle condition.

22. (currently amended) An network transmission system according to claim 17, wherein said isolation instruction information further comprises ~~in no signal~~ a no-signal condition caused by stopping the transmission of said optical transmitter due to a fault condition.

23. (original) An network transmission system according to claim 17, wherein said node, upon occurrence of said obstacle, prepares as said isolation instruction any of the following:

said isolation instruction information is said overhead indicating that said received synchronous multiplex signals are both in signal obstacle conditions,

said isolation instruction information is said overhead instructing a ring switch, in which synchronous multiplex signals are transmitted upon reception,

said isolation instruction information is overhead indicating that said synchronous multiplex signals to be transmitted are in a signal obstacle condition, and

said isolation instruction information is a no output signal condition caused by stopping the transmission of said optical transmitter.

24. (currently amended) A method for recovering from a plurality of substantially contemporaneous faults in a network node, said network node capable of transmitting information as synchronous multiplex signals via a plurality of transmission lines, including a first one and a second one, said method comprising:

preparing isolation information into an instruction signal according to said plurality of substantially contemporaneous faults, wherein said node experiencing said faults prepares said isolation information itself;

providing said isolation information to at least one of a plurality of adjacent network nodes; and

switching said transmission lines based upon said instruction signal so that said synchronous multiplex signals may be transmitted to either of said transmission lines properly.

25. (original) The method of claim 24, wherein, upon occurrence of said plurality of substantially contemporaneous faults, said preparing said isolation information further comprises any of the following:

said isolation instruction information comprises an overhead that indicates that received synchronous multiplex signals are in signal obstacle conditions,

said isolation instruction information comprises an overhead that instructs a ring switch, in which synchronous multiplex signals are transmitted upon reception,

said isolation instruction comprises an overhead that indicates that synchronous multiplex signals to be transmitted are in a signal obstacle condition, and

said isolation instruction information comprises a no output signal condition caused by stopping transmission of an optical transmitter within said node.

26. (original) The method of claim 24, wherein said network further comprises a SONET network.

27. (original) The method of claim 26, wherein said SONET network is a 2 fiber BLSR network.

Application No. 09/589,526
Amendment dated December 16, 2003
Reply to Office Action of June 17, 2003

PATENT

original.
28. (original) The method of claim 26, wherein said SONET network is a 4
fiber BLSR network.
